

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): An optical recording method for recording information in an optical recording medium comprising a grooved light-transparent substrate including grooves and lands and a phase change recording layer thereon, by irradiating a laser beam thereto through an objective lens in an optical system, wherein

the recording is carried out in a groove recording mode, in which only the grooves serve as a recording track, under the conditions:

$$0.48 \leq P_T/(\lambda/NA) \leq 0.74 \text{ and } P_T \leq 0.50 \text{ } \mu\text{m},$$

provided that the laser beam used for recording has a wavelength  $\lambda$ , the objective lens has a numerical aperture NA, and recording tracks are arranged at a pitch  $P_T$ , and wherein the grooves are located relatively closer to a plane through which the laser beam enters than the lands.

Claim 2 (Original): The optical recording method of claim 1 wherein the medium is operated at a linear velocity of at least 4.5 m/s.

Claim 3 (Original): The optical recording method of claim 1 wherein the recording forms a recorded mark having at least one end extending out of the groove.

Claim 4 (Original): The optical recording method of claim 1 wherein said optical recording medium includes the recording layer, a dielectric layer, and a reflective layer stacked on the light-transparent substrate in the described order,

the reflective layer has a thermal conductivity of at least 100 W/mK, and the dielectric layer has a thermal conductivity of at least 1 W/mK.

Claim 5 (Currently Amended): An optical recording method for recording information in an optical recording medium comprising a grooved light-transparent substrate and a phase change recording layer thereon, by irradiating a laser beam thereto through an objective lens in an optical system, wherein

the recording is carried out in a groove recording mode, in which only grooves serve as a recording track, under the condition:

$$0.48 \leq P_T/(\lambda/NA) \leq 0.68,$$

provided that the laser beam used for recording has a wavelength  $\lambda$ , the objective lens has a numerical aperture NA, and recording tracks are arranged at a pitch  $P_T$ ,

wherein the recording forms a recorded mark having at least one end extending out of the groove, and

wherein said optical recording medium includes the recording layer, a dielectric layer, and a reflective layer stacked on the light-transparent substrate in the described order,

the reflective layer has a thermal conductivity of at least 100 W/mK, and the dielectric layer has a thermal conductivity of at least 1 W/mK.

Claims 6-7 (Canceled).

Claim 8 (Original): An optical recording medium in which recording is carried out by the method of claim 1.

Claim 9 (Original): An optical recording medium in which recording is carried out by the method of claim 5.